[redacted]

Klassifikation gemäss den
VKF-Prüfbestimmungen Hagelregister

VKF Hagelschutz Nr. 40333

Inhaber /-in
Gokin Solar (HongKong) Company Limited
Lockhart Road 54-62
999077 Wanchai, HK
China

Hersteller /-in
Guangzhou Gokin Solar Technology Co Ltd
510800 Guangdong
China

Gruppe	121 - Dach - Photovoltaik Module
Produkt	GK-1-72HTBD-xxxM; GK-1-54HTBD-xxxM; GK-4-66HTBD-xxxM; GK-4-54HTBD-xxxM; GK-4-48HTBD-xxxM; GK-3-72HGBD-xxxM; GK-3-54HGBD-xxxM; GK-3-54HGDb-xxxM; GK-5-60HGBD-xxxM; GK-5-60HGDb-xxxM; GK-5-54HGBD-xxxM; GK-5-54HGDb-xxxM
Beschreibung	Glas-Glas Photovoltaikmodul. Frontglas vorgespannt/teilvorgespannt, Stärke = 2,0 mm. Rückseitenglas vorgespannt/teilvorgespannt, Stärke = 2,0 mm. Umlaufender Rahmen aus Aluminium, Höhe = 30 mm. xxx bezeichnet die Leistung in Wp. Die Anerkennung bezieht sich auf den solaren Teil und alle erhältlichen Leistungsklassen.
Unterlagen	-: Bestätigung Hersteller '20251203' (3. Dezember 2025)
VKF Prüfbestimmungen	Beschluss B Beschluss für die Zuordnung von nach IEC- und ISO-Normen geprüften solaren Elementen zu einer Hagelwiderstandsklasse, Version 1.04 vom 01.11.2016
Klassifikation Beurteilung	Hagelwiderstand Funktionalität HW 3
Bemerkungen	
Gültigkeitsdauer	31.12.2030
Ausstellungsdatum	22.12.2025
Ersetzt Dokument vom	

Vereinigung Kantonaler Feuerversicherungen

Die Funktionalität ist der minimale Hagelwiderstand von den Bauteilfunktionen:

Lichtdurchlässigkeit	HW --	Mechanik	HW --
Lichtabschirmung	HW --	Wasserdichtheit	HW --